J\$17 Res'd POT/PTO 2 5 APR 2001

FO	M PT	O-1390 L	S. DEPARTMENT (OF COMMERCE PATENT AND TRADEMARK OF	FICE ATTORNEY'S DOCKET N	UMPER Z 3 APR ZUUI				
(RE	V 11-2	2000)				36-1441				
		TRANSI	NITTAL LETTE SNATED/FLF(R TO THE UNITED STATES CTED OFFICE (DO/EO/US)	U.S. APPLICATION NO. (If					
		CONC	ERNING A FIL	ING UNDER 35 U.S.C. 371	0 7	uhk8.3027 1 1				
INT	ERN,	PCT/GB99/0		INTERNATIONAL FILING DATE 17 November 1999	PRIORITY DATE CLAI 25 N	MED lovember 1998				
ТІТ	LE C	F INVENTION								
				MESSAGING PLATE	ORM					
AP	PLIC	ANT(S) FOR E	OO/EO/US	BALE et al						
App	olicar	nt herewith sub	mits to the Unite	d States Designated/Elected Office (D	O/EO/US) the following items	and other information:				
1.	\boxtimes			of items concerning a filing under 35 U						
2.				EQUENT submission of items concern		71.				
3.	\boxtimes	This is an ex		begin national examination procedure						
4.	\boxtimes	The U.S. ha	s been elected b	by the expiration of 19 months from the	priority date (Article 31).					
5.	Ac			ation as filed (35 U.S.C. 371(c)(2)).	,					
(D)	a.	⊠ is attac	hed hereto (req	uired only if not communicated by the I	nternational Bureau).					
Ų.j	b.			ed by the International Bureau.	,					
	c.	☐ is not r	equired, as the a	application was filed in the United State	s Receiving Office (RO/US).					
0				tion of the International Application as t						
14	a.		hed hereto.							
3	b.	☐ has be	en previously su	bmitted under 35 U.S.C. 154(d)(4).						
THE WAY		Amendments	s to the claims o	f the International Application under PC	T Article 19 (35 U.S.C. 371(c)(3))				
TU	a.	are attached hereto (required only if not communicated by the International Bureau).								
M	b.	have be	en communicat	ed by the International Bureau.						
A COLUMN	C.	have no	ot been made; h	owever, the time limit for making such a	amendments has NOT expired	i.				
7	d.	have no	ot been made ar	nd will not be made.						
8.		An English la	inguage translat	ion of the amendments to the claims u	nder PCT Article 19 (35 U.S.C	. 371(c)(3)).				
9.	\boxtimes			inventor(s) (35 U.S.C. 371(c)(4)).						
10.		A English lan Article (guage translatio 36 (35 U.S.C. 37	on of the annexes of the International P 1(c)(5)).	reliminary Examination Repor	t under PCT				
	lten	ns 11 To 20 b	elow concern d	ocument(s) or information included						
11.				atement under 37 C.F.R. 1.97 and 1.98						
12.	\boxtimes	An assignme	nt document for	recording. A separate cover sheet in c	ompliance with 37 C.F.R. 3.28	8 and 3.31 is included				
13.	\boxtimes		iminary amendr			and the state of t				
14.		A SECOND of	r SUBSEQUEN	T preliminary amendment.						
15.		A substitute s	pecification.							
16.		A change of p	ower of attorne	and/or address letter.						
17.		A computer-re	adable form of	the sequence listing in accordance with	PCT Rule 13ter.2 and 35 U.S	S.C. 1.821-1.825.				
18.		A second co	py of the publi	shed international application unde	r 35 U.S.C. 154(d)(4)					
19.		A second cop	y of the English	language translation of the international	al application under 35 U.S.C.	154(d)(4)				
20.		Other items o								

U.S. APPLICATION NO/(If A	w3027	R 1.5)	INTERNATIONAL APPLICA PCT/GB99/0383			ATT	TORNEY'S DOCKET NUMBER 36-1441	
21. The following f	ees are submi	tted:				Гc	ALCULATIONS	PTO USE ONLY
BASIC NATIONAL	FEE (37 C.F.I	R. 1.492(a)(1)-(5):			Ť		
Neither internation	onal prelimina	ry examinat	ion fee (37 C.F.R. 1.482)			ı		
			145(a)(2)) paid to USPTÓ			ı		
and Internationa	and International Search Report not prepared by the EPO or JPO\$1000.00							
International pre USPTO but Inter	International preliminary examination fee (37 C.F.R. 1,482) not paid to USPTO but International Search Report prepared by the EPO or JPO\$860.00							
International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO\$710.00								
International preliminary examination fee (37 C.F.R. 1,482) paid to USPTO								
International prei	but all claims did not satisfy provisions of PCT Article 33(1)-(4)							
and all claims sa	tisfied provision	ns of PCT	Article 33(1)-(4)	\$1	00.00	L		
			ENTER APPROPRIATE	BASIC FEE AI	= TNUON	\$	860.00	
Surcharge of \$130.00 for months from the earlies	or furnishing th	e oath or d	eclaration later than 20	□ 30		\$	0.00	
CLAIMS	NUMBER	R FILED	NUMBER EXTRA	RATE		3	0.00	
Total Claims	17	-20 =			18.00	s	0.00	
Independent Claims	2	-3 =			80.00	٥		
MULTIPLE DEPENDEN	T CLAIMS(S)	(if applicab	le)	\$270.0		s	0.00	
	1 02 1110(0)	(п арриоар		OVE CALCULA		\$	860.00	
Applicant claims sr	nall entity stat	us. See 37	CFR 1.27. The fees indicate	ated above	110113 -	φ	000.00	
are reduced by 1/2							0.00	
I.				SUB	TOTAL =	ŝ	860.00	
Processing fee of \$130.	00, for furnish	ng the Eng	ish Translation later than	720 [730		Ť	000.00	
months from the earliest	claimed prior	ity date (37	C.F.R. 1.492(f)).	+			0.00	
TOTAL NATIONAL FEE =						s	860.00	
Fee for recording the en	closed assign	ment (37 C	F.R. 1.21(h)). The assignr	nent must be				
accompanied by an app	ropriate cover	sheet (37 (C.F.R. 3.28, 3.31). \$40.00	er property	+	\$	40.00	
Fee for Petition to Reviv	e Unintentiona	ally Abando	ned Application (\$1240.00	Small Entity =	\$620.00)	\$	0.00	
7				AL FEES ENC	LOSED =	\$	900.00	
6						Α	mount to be:	
- A							refunded	\$
							Charged	\$
a. A check in the amount of \$900.00 to cover the above fees is enclosed. b. Please charge my Deposit Account No. 14-1140 in the amount of \$ to cover the above fees. A duplicate copy of this form is enclosed. c. The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 14-1140. A fulplicate copy of this form is enclosed. d. The entire content of the foreign application(s), referred to in this application is/are hereby incorporated by reference in this application. NOTE: Where an appropriate time limit under 37 C.F.R. 1.494 or 1.495 has not been met, a petition to revive (37 C.F.R. 1.137(a) or (b)) must be filled and granted to restore the application to pending status. SEND ALL CORRESPONDENCE TO: NIXON & VANDERHYE P. C. 1100 North Glabe Road, 8 th Floor Arlington, Virginia 22201-4714 Telephone: (703) 816-4000 Larry S. Nixon NAME								
				25,640			April 25, 200	01
				REGISTRATI	ON NUMBE	в —	Date	

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

BALE et al

Atty. Ref.: 36-1441

Serial No. Unknown

Group:

National Phase of:

PCT/GB99/03831

International Filing Date: 17 November 1999

Filed:

April 25, 2001

Examiner:

For:

MESSAGING PLATFORM

April 25, 2001

Assistant Commissioner for Patents Washington, DC 20231

Sir:

PRELIMINARY AMENDMENT

Prior to calculation of the filing fee and in order to place the above identified application in better condition for examination, please amend the claims as follows:

IN THE CLAIMS

Please substitute the following amended claims for corresponding claims previously presented. A copy of the amended claims showing current revisions is attached

- 5. (Amended) A platform according to claim 3 in which the criteria apply a class of service selected depending on the identity of a subscriber mailbox to which the control request applies.
- 6. (Amended) A platform according to claim 3, in which the criteria apply different service classes depending on the transaction requested by the control request.
 - 7. (Amended) A message system comprising:
 - a service platform running a message service application; and

a messaging platform according to claim 1 connected to the service platform via a control interface, and arranged to receive control requests from the service platform via the control interface.

- (Amended) A communications network including a messaging platform according to claim 1.
- 14. (Amended) A method according to claim 12, including applying different classes of service to control requests depending on identities of customer mailboxes to which the control requests apply.
- 15. (Amended) A method according to claim 12, including applying different classes of service to control requests depending on the transaction requested by the control request.

Please add new claim 17 as follows:

17. (New) A communications network including a messaging system as in claim7.

REMARKS

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page is captioned "Version with markings to show

changes made."

The above amendments are made to place the claims in a more traditional format.

Respectfully submitted,

NIXON & VANDERHYE P.C.

By:

Larry S. Nixon

LSN:Imy

1100 North Glebe Road, 8th Floor Arlington, VA 22201-4714 Telephone: (703) 816-4000 Facsimile: (703) 816-4100

VERSION WITH MARKINGS TO SHOW CHANGES MADE

- 5. (Amended) A platform according to claim 3 [or 4] in which the criteria apply a class of service selected depending on the identity of a subscriber mailbox to which the control request applies.
- (Amended) A platform according to [any one of claims 3 to 5] <u>claim 3</u>, in which the criteria apply different service classes depending on the transaction requested by the control request.
 - 7. (Amended) A message system comprising:
 - a service platform running a message service application; and
- a messaging platform according to [any one of the preceding claims] claim 1 connected to the service platform via a control interface, and arranged to receive control requests from the service platform via the control interface.
- 9. (Amended) A communications network including a messaging platform according to [any one of claims 1 to 6 or a messaging system according to claim 7 or 8] claim 1.
- 14. (Amended) A method according to claim 12 [or 13], including applying different classes of service to control requests depending on identities of customer mailboxes to which the control requests apply.
- 15. (Amended) A method according to claim 12, [13 or 14,] including applying different classes of service to control requests depending on the transaction requested by the control request.

5

20

TOURSON TANDAMON

MESSAGING PLATFORM

The present invention relates to a messaging platform suitable for use in a communications network.

Users of communications networks are now commonly offered a variety of messaging services. By contrast with conventional telephony services in which calls are established in real time, in messaging services a message, which may be in any of a number of media, is deposited at one time and read at a later time. These services may include, for example, voicemail allowing the user to record a 10 spoken message, faxmail that similarly allows a fax to be stored for later retrieval by the addressee, or email

According to a first aspect of the present invention, there is provided a messaging platform including

a) a message store arranged to receive message data and to store said 15 message data for subsequent retrieval, characterised by

b) an overload controller responsive to an overload condition in the platform and arranged, in response to the said overload condition, to limit loading of the platform

While it is known to provide platforms for real-time telephony with overload control mechanisms, conventionally messaging platforms have been regarded as carrying out an "off-line" data storage and processing function and so have not included such overload control mechanisms. The present inventors have found however that the addition of an overload controller to a messaging platform 25 significantly enhances the stability and scaleability of the platform, that is to say its ability to adapt to increasing numbers of users.

The term "overload condition" as used in this document encompasses conditions in which the loading of the platform is approaching a level at which the operation of the platform would be impaired, as well as conditions in which such a 30 level has already been reached. In general the overload controller will be arranged to limit the loading of the platform is such a way that the level at which impairment occurs is not reached.

Preferably the platform further comprises

c) a control interface arranged to receive control requests instructing transactions on the messaging platform, and the overload controller includes means for denying at least some of the control requests in response to the overload condition.

While at one time the messaging platforms supporting such services were operated solely under the control of the network operator, increasingly messaging services are operated by service providers other than the network operator. Accordingly it is necessary to provide the messaging platform with a control interface to allow communication of control signals with the service provider. In addition, in order to implement more advanced services which go beyond mere 10 message deposit and retrieval, it necessary to provide users with some access to a control interface. The present inventors have recognised that overloading of the control interfaces on a messaging platform is a critical factor in degrading the reliability of such platforms. This preferred feature of the invention, by providing an overload controller on the control interface significantly enhances the performance of the platform and makes it possible to open control interfaces to service providers or to users without compromising the stability of the platform.

Preferably the overload controller includes a store programmed with criteria for applying different classes of service to (a) the mailboxes in the mail store, (b) the service providers accessing the mail store, (c) control messages at 20 the control interface, or any combination of these. The overload controller is arranged, in response to an overload condition on the platform or the service provider, selectively to deny access to a control message depending on a class of service assigned in accordance with the said criteria to the control message.

Preferably the messaging platform includes a plurality of mailboxes containing message data, each mailbox being switchable between an open state, in which message data may be written to or read from the mailbox, and a closed state, and the overload controller is arranged to allow requests for the closing of a mailbox and to deny requests for the opening of the mailbox.

The inventors have found that a particularly effective means of limiting the 30 loading of the platform, while also limiting the impact on ongoing transactions, is to admit requests for closing mailboxes and to deny requests for opening mailboxes. Since requests for opening mailboxes are normally followed by a number of related transactions, denying these requests, while allowing existing

5

15

transaction sequences to be terminated by the closing of a mailbox, quickly results in a reduction in the loading of the platform.

According to a second aspect of the present invention, there is provided a messaging system comprising:

a service platform running a messaging service application; and

a messaging platform in accordance with the first aspect connected to the service platform via a control interface, and arranged to receive control requests from the service platform via the control interface.

The service platform may be integrated with the messaging platform, but 10 preferably is remote from it. Several such service platforms may communicate with a single messaging platform.

According to a third aspect of the present invention, there is provided a method of operating a messaging platform including:

a) storing message data on the messaging platform;

b) subsequently outputting message data from the platform, thereby allowing retrieval of a corresponding message;

characterised by

c) detecting an overload condition on the platform and in response to the overload condition limiting loading of the platform.

20 Systems embodying the present invention will now be described in further detail, by way of example only, with reference to the accompanying drawings, in which;

Figure 1 is a schematic of a network incorporating a messaging platform;

Figure 2 is a schematic of a platform embodying the invention for use in 25 the network of Figure 1;

Figures 3a to 3y are SDL diagrams showing in further detail the platform of Figure 2; and

Figure 4 is a diagram showing in further detail the platform of Figure 2.

As shown in Figure 1, a communications system includes a messaging platform 1. The messaging platform 1 is connected to a service provider platform 2. The service provider platform is connected to a number of communications networks including an IP (internet protocol) network 3 and the PSTN (public switched telephone network) 4. Customer terminals 5,6,7 are connected to the service provider platform variously via the PSTN and via the IP network. The

customer terminals may include for example, conventional fixed-line telephones, mobile telephones and also personal computers.

In use, customers may subscribe to a message service offered by the service provider. Then, for example, when a subscriber is not able to take a call from a calling party, the call may be diverted to the service provider platform. The service provider platform may then communicate data received from the caller, for example in the form of a recorded digitised voice message, to the messaging platform.

Figure 2 shows in further detail the messaging platform. This may be implemented, for example, using the BT CallMinder platform (described in [British Telecom Engineering Vol 15 Part 2 July 1996]), which is based on the Speech Applications Platform (described in [British Telecom Engineering Vol 13 Part 4 January 1995]). The CallMinder platform is an integrated platform implementing both a service application platform and the messaging platform. Alternatively a distributed architecture may be used in which a number of service provider platforms communicate with a message platform over a network. In this case, a suitable architecture is that described in Messaging APIs for Voice Networks, RM Claxton, Sixth IEE Conference on Telecommunications (no. 451) 1998.

As shown in Figure 2, a number of service providers, A,B,...m are 20 connected to the messaging platform by control and data channels. As noted in the introduction above, some end users may themselves be given access to the control interface of the messaging platform, and the term "service provider" is used here broadly to encompass any party accessing the control interface, including such end users. The control channels are used for registration 25 commands, for example to set event detection triggers on the platform to generate a notification whenever a message is left for a specified subscriber, and for action commands, for example to carry out actions such as replaying a message, saving a message or deleting a message. Both data and control channels from the service providers pass in the first instance to an access controller. The access controller is 30 connected to an overload controller. The overload controller and access controller in combination function to protect the platform from overloading by signals arriving on the service provider interface. The overload controller detects overload conditions, for example by monitoring the rate of transactions between the access controller and service providers or alternatively by monitoring the processor utilisation of the mail store processors. When an overload condition is detected by the overload controller then the overload controller configures the access controller to deny access to the platform to certain signals (for example, requests to open a low priority mailbox in the mail store). Different types of signals are assigned different priorities. Three alternative schemes are described below by way of example.

Scheme 1

In this scheme, different service classes are applied to different service providers. During overload conditions, as monitored by a load controller, those subscribing to a higher priority class of service level agreement are given priority over those requests coming from a Service Provider with a lower priority class. Hence, actions pertaining to the particular mailboxes used by customers of the higher priority class of service would receive preferential treatment. It is envisaged that a range of service classes will be defined, which will correspond to the overload mechanism achieving a specified quality of service for those classes. Examples of service classes are given in Table 1 below.

Service	Description							
Class								
Œ.	Guaranteed end user access 99.99% of the time							
	Guaranteed Service Provider notifications within 30 seconds,							
	99.99% of the time							
II Guaranteed end user access 98.0 % of the time								
	Guaranteed Service Provider notifications within 30 seconds,							
	90.0% of the time							
	Guaranteed Service Provider notifications within 20 minutes,							
	99.99% of the time							
1#	No guaranteed end user access							
	No guaranteed Service Provider notifications							

Scheme 2

As in scheme 1 different service classes are used. In this case the different
20 service classes are applied to individual mailboxes for particular subscribers.

Mailbox subscribers subscribing to higher service level classes are given priority

over requests for action associated with individual mailbox users with a lower priority class,

Scheme 3

5 In this scheme, different priorities are applied to certain types of transaction across the service provider interface. For example, the ability to deposit a message from a caller into a mailbox could take priority over a change of profile request from the user depending upon the load conditions prevailing.

As a further alternative, elements of two or more of these schemes may 10 be combined, so that the priority given to a certain signal at the service provider interface may depend upon a weighted combination of the service provider class, the subscriber class and the signalling type priority.

A service provider application which itself becomes overloaded may also request that the mail system imposes an overload control scheme (such as those 15 described above) to protect that application from overload.

In operation, which ever scheme is used, the overload controller monitors an appropriate one or more loading parameters. In the present example this parameter is the rate of transactions between the service provider applications and the mailboxes which pass through the access controller. This mechanism provides 20 a measure of mail system processing usage. Other examples of measuring processing load may be based on directly measuring the load on the platform Central Processor Units and other hardware devices (this information is usually available from operating systems). Alternatively, other load measures, such as the amount of storage utilised (disk and memory) can be measured. Again this 25 information is provided by most operating systems (e.g. Windows 95 and UNIX both provide system information). Threshold levels for system loading are defined for the mail system. The thresholds are defined such that a defined quality of service can be met for particular service classes (seeTable 1), and are dependent upon the platform and Mail system being used, and the customer/service mix for 30 the particular implementation. As these threshold levels are reached, the overload control management imposes overload control. The following controls can be imposed:

- · refusing new requests by Service Providers to open low priority mailboxes,
- · closing Service Provider access to low priority open mailboxes,

- · refusing end user access to low priority mailboxes,
- queuing control messages and data transfers on the next highest priority open mailhoxes

If the next load threshold level is reached, the same overload controls will be imposed on the next highest priority mailboxes. If instead, the system load reduces, the overload controls set at that level are removed in reverse order to that in which they were applied.

In addition to responding to overload conditions within the platform, the overload controller may also be programmed to recognise and respond to signals

10 from a service platform indicating that that platform is overloaded. The overload controller might then, for example, inhibit the transmission of notifications from the messaging platform to the overloaded service platform.

Figures 3a to 3y are SDL (Specification and Description Language [ITU-T Z.100]) diagrams showing in further detail the implementation of the messaging platform, including the overload controller. The structures shown may be compiled using commercially available software tools to provide code for running on the processors of the messaging platform. A description of the SDL diagrams follows:

20 Figure 3a: Diagram Structure

Describes the structure of the following figures 3b to 3v.

Figures 3b-3d: System mail system 1-3

Defines the static limits of the described mail system, and type definitions and operators for variables used.

Figure 3e: System mail system 4

Defines all of the control signals used in the mail system.

30 Figure 3f: System mail system 5

Defines the two main blocks of the system: the mail application block (i.e. the service provider platform) and the mail system block (i.e. the messaging platform). The interfaces between the blocks (the mail system API), and to/from the external environment are also defined.

5

Figure 3g: Block mail application block 1

Defines the processes and interfaces within the mail application block. In this case, only the mail application processes are defined.

Figure 3h-3j: Process mail application 1-3

Defines all of the control signals, variables, states, states transitions and actions of the mail application necessary to illustrate the present invention. The process contains one state ('alive'), and acts on a number of events as follows:

10 user_mailbox_open: A request from a user (or some other stimulus) to open a mailbox results in a request to the access controller to open a mailbox.

user_mailbox_close: A request from a user (or some other stimulus) to close a mailbox results in a request to the access controller to close a mailbox.

user_mailbox_request: A request from a user (or some other stimulus) to perform
15 an action on an open mailbox usually results in a request to the access controller
to perform an action on an open mailbox. If however, the mail system is overloaded, then the request will be queued.

mail_application_overload_detected: An indication from the service provider platform (or some other stimulus) that the mail application is overloaded results in a request to the access controller to impose overload controls on open mailboxes opened by that application that are below a specified service class. Requests to these mailboxes are not queued.

mail_application_overload_ceased: An indication from the service provider platform
 (or some other stimulus) that the mail application overload has ceased results in a
 request to the access controller to remove overload controls on open mailboxes opened by that application that are above a specified service class.

UM opened: Confirms that a mailbox has been opened.

UM_closed: Confirms that a mailbox has been closed.

UM_open_denied: Indicates that a request to open a mailbox has been denied - for 30 example because overload controls have been imposed.

UM_notification: Indicates a notification from a mailbox, which is passed back to the application user (if appropriate). The notification could be the result of an earlier mail application request on the mailbox, or another (e.g., timer) event. queue_UM_requests: Indicates that the access controller has imposed overload controls on a mailbox, and that the mail application should not make further requests on that mailbox. The mail application will queue subsequent requests.

resume_UM_requests: Indicates that the access controller has removed overload controls on a mailbox, and that the mail application can make further requests on that mailbox. Any pending requests in the queue will be immediately sent to the mail system.

Figure 3k: Block mail_system_block 1

10 Defines the processes and interfaces within the mail system block. In this case, there are three processes: the single access controller, the single overload controller, and the multiple user mailboxes.

Figure 3I-3p: Process access controller 1-5

- 15 Defines all of the control signals, variables, procedures, states, states transitions and actions of the access controller necessary to illustrate the present invention. The process contains one state ('alive') that is entered after the 'tr_timer' has been set. The process acts on a number of events as follows:
- UM_open: A request from a mail application to open a mailbox is received. The transaction counter is incremented. If the mailbox has a higher priority ('class') than that set by the overload control mechanism, the mailbox is opened (by creating a user mailbox process), the identity of the mailbox is added to the linked list of open mailboxes, and the actions are confirmed to the mail application. Otherwise, the mail application is informed that the request is denied.
- 25 UM_close: A request from a mail application to close a mailbox is received. The transaction counter is incremented. The mailbox is closed by terminating the user mailbox process, the identity of the mailbox is removed from the linked list of open mailboxes, and the actions are confirmed to the mail application.
- UM_request: A request from a mail application to perform an operation on an open an amilbox is received. The transaction counter is incremented. If the overload control is not applied to that mailbox, then the request is passed onto the mailbox. Otherwise, the request is placed in an request queue.
 - set_UM_class_bar: A request from the overload controller to set the priority level ('class') at which mailboxes may be opened or controlled is received. If the priority

level is higher than the current priority level (the 'current_class_bar'), then mail applications with open mailboxes below the priority level are requested to queue further requests to that mailbox (procedure 'queue_transactions'), the current priority level is raised to the new level. If the priority level is lower than the current priority level (the 'current_class_bar'), then any queued requests received from mail applications are unqueued (procedure 'unqueue_requests'). Following this, mail applications with open mailboxes above the priority level are requested to resume further requests to that mailbox (procedure 'resume_transactions'), and the current priority level is lowered to the new level.

10 notification: A notification from an open mailbox is received. The transaction counter is incremented, and the notification is passed on to the relevant mail application.

impose_UM_load_control: A request from a mail application to impose load control on open mailboxes that were opened by the application is received. Mailboxes with a class less than or equal to the specified level are requested to queue up notifications, if not already doing so. Mailboxes with a class greater than the specified level are requested to resume notifications, if not already asked to do so. This mechanism does not override any controls imposed by the overload controller. tr_timer: A transaction timer expiry event is received. The transaction timer is set

20 to expire every second. The current transaction rate is thus the value of the transaction counter, per second. This overload controller is informed of the current transaction rate, the transaction counter is reset to zero and the tr timer reset.

Figure 3q: Procedure get UM class 1

25 Defines the procedure for retrieving the provisioned service class of a mailbox from the management system for the mail system.

Figure 3r: Procedure queue transactions 1

Defines the procedure for informing the mail application to queue requests to open 30 mailboxes, and informing the mailbox to queue notifications, when overload controls are imposed.

Figure 3s: Procedure resume transactions 1

Defines the procedure for informing the mail application to queue requests to open mailboxes, and informing the mailbox to queue notifications, when overload 5 controls are imposed.

Figure 3t: Procedure unqueue requests 1

Defines the procedure for unqueueing requests for operations on mailboxes when overload controls have been removed.

10

Figure 3u: Process overload_controller 1

Defines all of the control signals, variables, procedures, states, states transitions and actions of the overload controller necessary to illustrate the present invention.

The process contains one state ('monitoring') that is entered after the threshold levels for the overload controls have been set in the threshold levels table. The process acts on a number of events as follows:

transaction_rate: An indication of the current transaction rate at the access controller is received. If this rate has fallen below the current minimum level, then the current overload priority ('UM_class_bar') is decremented (if it is not already at 20 the lowest level). The threshold levels are then adjusted accordingly – from the threshold table, and the access control is requested to reduce or remove the overload control. If, alternatively, the rate has risen above the current maximum level, then the current overload priority ('UM_class_bar') is incremented (if it is not already at the highest level). The threshold levels are then adjusted accordingly and

25 the access control is requested to increase the level of overload control.

Figure 3v: Procedure set thresholds 1

Defines the procedure for setting the threshold levels in the overload control threshold table. These levels define the points at which the oveload controls will 30 be imposed or removed.

Figure 3w-3x: Process user mailbox 1-2

Defines all of the control signals, variables, procedures, states, states transitions and actions of the user mailbox necessary to illustrate the present invention. The process contains one state ('alive'), and acts on a number of events as follows:

5 queue_notifications: An request to queue notifications is received from the access controller. A flag is set indicate that future notifications should be queued.

resume_notifications: An request to resume notifications is received from the access controller. A flag is cleared indicate that future notifications should no longer be queued, and any queued notifications are unqueued.

10 request: An request to perform an operation is received from the mail application via the access controller. The operation is performed as requested (procedure 'perform_request').

event: An indication that an event has occurred in the mailbox (e.g. the result of an operation or a timer expiry) is received. If overload control has been imposed,
 then the notification of the event to the mail application is queued. Otherwise, the notification is sent to the mail application via the access controller.

stop_mailbox: An request to stop the user mailbox process is received from the access controller. The user mailbox process terminates, closing the mailbox.

20 Figure 3y: Procedure perform_request 1

Defines the procedure for the mailbox to perform an operation requested by the mail application.

Figure 4 illustrates an example of hardware systems used to implement
25 the present invention. It will be understood that the components and architecture
shown here are given by way of example only, and many alternative components
and architectures may be used equivalently. For example, rather than using
platforms built from rack-mounted processors and storage devices, some or all of
the platforms might be implemented on computer workstations. Such
30 workstations may be joined together by a network to provide a distributed
computing system. As a further example of the alternatives available, storage
devices are by no means limited to conventional hard disks, but might alternatively
or in addition use magneto-optical or optical storage media. Also, as previously
stated, one or more of the "service platforms" may be embodied in a customer

terminal that exercises a control function, for example in a personal computer, or in a so-called internet appliance such as a television set-top box arranged to provide Internet access, or in an intelligent telephone that provides the necessary control capabilities.

In Figure 4, end users connect to the Service Provider platform by telephone or computer. One or more Service Provider platforms are connected to the Mail Store platform. The Service Provider platform runs the mail applications (for example to collect messages, and permit retrieval of messages), interfaces to the end users, and sends control and data signals to the Mail Store platform to store and retrieve messages held in electronic format.

It is possible that the Service Provider platform and Mail Store Platform reside on the same computing node. In this case the buses B1 and B2 can be joined directly, therefore removing the need for interface I3, the Mail Store interface shelf (S3) and the Service Provider interface shelf (M3). Alternatively the platforms may be connected to each other via a network, for example the Internet, an ATM network, or a local area network LAN.

A description of the system follows:

20 Interfaces

Interface I1: This is a standard telephony interface, which allows end users to record or retrieve voice messages. The interface will usually be provided via a telephony network.

25 Interface I2: This is an electronic data interface to a computer (e.g. TCP/IP), which allows end users to record or retrieve voice or electronic messages. The interface will usually be provided via a data network such as the internet.

Interface I3: This is an electronic data interface which transports the control and data signals between the Service Provider and Mail Store platforms. This is typically implemented as an ethernet, frame-relay or X.25 data link, running the TCP/IP protocol. Control and Data messages may be carried using suitable protocols, such as the Internet File Transfer Protocol (FTP).

5

10

Interface I4: This is an electronic data interface to the Service Provider platform management system (for example, a customer management system or simply a computer terminal). The protocol used with this interface will typically be the internet Simple Network Management Protocol (SNMP) running over TCP/IP.

Interface I5: This is an electronic data interface to the Mail Store platform management system (for example, a network management system or simply a computer terminal). The protocol used with this interface will typically be the internet Simple Network Management Protocol (SNMP) running over TCP/IP.

Interface I6: This is an electronic data interface which transports the control and data signals between the Mail Store platforms. This allows the Mail System to be distributed across a number of sites (e.g. for resilience and performance reasons). This is typically implemented as a frame-relay or X.25 data link, running the TCP/IP protocol. Control and Data messages may be carried using suitable protocols, such as the Internet File Transfer Protocol (FTP).

Service Provider Platform Components

20 The Service Provider platform comprises a number of shelves, which are specialised to meet particular needs, and a bus (bus B1) that connects the shelves. A shelf is either a processor shelf (consisting of processor, memory, clocks, I/O devices, etc.) or a storage shelf (consisting of hard disk storage, disk controllers, etc.).

25

Shelf S1: Mail Applications Processor shelf.

This runs the various applications that interface the end users and other applications to the mail system.

30 Shelf S2: Platform Management Processor shelf.

This runs the necessary management applications for the service provider platform, and interfaces to an external management system via 14.

Shelf S3: Mail System Interface Processor shelf.

This provides the physical termination of the interface (I3) to the Mail System platform, and runs the software to interface the protocols to the rest of the Service Provider platform.

5 Shelf S4: Interactive Voice Response Processor shelf.

This runs the software that interacts directly with end uses, usually over the telephony interface (I1) via the Telephony Interface processor shelf (although it can be used to interact with users over the internet interface). This shelf is able to play announcements to end users, and record voice messages into electronic format 10 (e.g. PC '.wav' format), that will ultimately be stored in the Mail System.

Shelf S5: Telephony Processor shelf.

This provides the physical termination of the interface (I1) to the telephony network, and runs the software to interface the protocols and bearer circuits to the 15 rest of the Service Provider platform.

Shelf S6: Internet Processor shelf.

This provides the physical termination of the interface (I2) to the internet network, and runs the software to interface the control and data protocols to the rest of the 20 Service Provider platform.

Shelf S7: Runtime Data Storage shelf.

Provides hard disk storage for the various processor shelves to use at run time.

25 Shelf S8: Audit Data Storage shelf.

Provides resilient hard disk storage for system data that needs to be held for logging and auditing purposes. This is usually stored by the processor shelves, and retrieved by the external management system via the Platform Management processor shelf (S2).

Mail Store Platform Components

30

The Mail Store platform comprises a number of shelves, which are specialised to meet particular needs, and a bus (bus B2) that connects the shelves. A shelf is

either a processor shelf (consisting of processor, memory, clocks, I/O devices, etc) or a storage shelf (consisting of hard (disk) storage, disk controllers, etc).

Shelf M1: Mailbox Controllers Processor shelf.

5 This runs the software used to store and retrieve messages and other information in user mailboxes.

Shelf M2: Platform Management Processor shelf.

This runs the necessary management applications for the service provider platform, 10 and interfaces to an external management system via I5.

Shelf M3: Service Provider Interface Processor shelf.

This provides the physical termination of the interface (I3) from one or more Service Provider platforms, and runs the software to interface the protocols to the 15 rest of the Mail System platform.

Shelf M4 Access and Overload Controller Processor shelf.

This runs the access controller and overload controller process software for the Mail System.

20

Shelf M5: Mail System Interface Processor shelf.

This provides the physical termination of the interface (I6) from one or more other Mail System platforms, and runs the software to interface the protocols to the rest of the Mail System platform.

25

Shelf M7: Mailbox Data Storage shelf.

Provides resilient hard disk storage for the user mailboxes. This is shelf is usually only accessed by the Mailbox Controllers shelf (M1) and the Platform Management processor shelf (M2).

30

Shelf M7: Runtime Data Storage shelf.

Provides hard disk storage for the various processor shelves to use at run time.

Shelf M8: Audit Data Storage shelf.

BUSINESS : BANKEROS

Provides resilient hard disk storage for system data that needs to be held for logging and auditing purposes. This is usually stored by the processor shelves, and retrieved by the external management system via the Platform Management processor shelf (M2).

5

CLAIMS

- 1. A messaging platform including:
- a) a message store arranged to receive message data and to store said
 5 message data for subsequent retrieval,

characterised by

 b) an overload controller responsive to an overload condition in the platform and arranged, in response to the said overload condition, to limit loading of the platform.

10

- 2. A messaging platform according to claim 1, further comprising:
- c) a control interface arranged to receive control requests instructing transactions on the messaging platform,

and in which the overload controller includes means for denying at least 15 some of the control requests in response to the overload condition.

- A platform according to claim 2, in which the overload controller is programmed with criteria for applying different classes of service to control requests received at the control interface and the overload controller is arranged, in
 response to an overload condition on the platform, selectively to deny control requests depending on a class of service assigned in accordance with the said criteria to the control request.
- A platform according to claim 3, in which the criteria apply a class of service
 selected depending on the identity of a service provider originating the said control requests
- A platform according to claim 3 or 4 in which the criteria apply a class of service selected depending on the identity of a subscriber mailbox to which the 30 control request applies
 - A platform according to any one of claims 3 to 5, in which the criteria apply different service classes depending on the transaction requested by the control request.

10

- 7. A messaging system comprising:
 - a service platform running a messaging service application; and
- a messaging platform according to any one of the proceeding claims

 5 connected to the service platform via a control interface, and arranged to receive
 control requests from the service platform via the control interface.
 - 8. A messaging system according to claim 7, in which the service platform is remote from the messaging platform.
 - A communications network including a messaging platform according to any one of claims 1 to 6, or a messaging system according to claim 7 or 8.
 - 10. A method of operating a messaging platform including:
- 15 a) storing message data on the messaging platform:
 - b) subsequently outputting message data from the platform, thereby allowing retrieval of a corresponding message;


characterised by


- c) detecting an overload condition on the platform and in response to the
 20 overload condition limiting loading of the platform.
 - 11. A method according to claim 10, further comprising
 - d) receiving at the message platform control requests instructing a transaction on the messaging platform,
- and in which the step of limiting loading of the platform includes denying at least some of the control requests.
- A method according to claim 11, including applying different classes of service to the control requests, and in response to the overload condition
 selectively denying some only of the control requests depending on the class of service applied to the control requests.

- 13. A method according to claim 12, including applying different classes of service to control requests depending on the identity of an originating service provider.
- 5 14. A method according to claim 12 or 13, including applying different classes of service to control requests depending on identities of customer mailboxes to which the control requests apply.
- 15. A method according to claim 12, 13 or 14, including applying different classes of service to control requests depending on the transaction requested by the control request
- 16. A method according to claim 15, in which the messaging platform includes a plurality of mailboxes containing message data, each mailbox being switchable between an open state, in which message data may be written to or read from the mailbox, and a closed state, and in which the step of limiting loading includes allowing requests for the closing of a mailbox and denying requests for the opening of a mailbox.

ABSTRACT

A messaging platform, for example a platform storing email or voicemail, is 5 provided with an overload controller which detects an overload condition and then acts to limit the loading of the platform. The overload controller may be associated with a control interface used, for example, for communication between a service provider and the message platform, and may selectively deny some of the requests received over that interface when the overload condition is detected.





3/28

Fig.3a.




Fig.3b.

4/28

System mail system

1(5)

______,

*/ Mail Overload System SDLS Version 1.1 Mel Bale / BT 17 November 1998 SYSTEM DIAGRAM

/* maximum number of mail applications */ SYNONYM MAX_APP integer = 100;

/* maximum number of user mailboxes */ SYNONYM MAX_MBOX linteger = 1000;

/* null value for user mailboxes */ SYNONYM MBOX_NULL integer = -1;

/* maximum number of service classes */
SYNONYM MAX_SERVICE_CLASS integer =4;

/*maximum length of an operation queue */
SYNONYM MAX_OPERATION_QUEUE integer = 10;

/*----*/

SYNONYM tr_dur duration = 1; /*1 second */ SYNONYM tr_duration integer = 1; /* as tr_dur */

SYNTYPE MBOX_ADDRESS = integer constants 0:MAX_MBOX ENDSYNTYPE MBOX ADDRESS;

SYNTYPE MBOX_POINTER = integer constants MBOX_NULL:MAX_MBOX ENDSYNTYPE MBOX_POINTER;

SYNTYPE SERVICE_CLASS = integer constants 0:MAX_SERVICE_CLASS ENDSYNTYPE SERVICE_CLASS;

SYNTYPE OPERATION_QUEUE_POINTER = integer constants 0:MAX_OPERATION_QUEUE ENDSYNTYPE OPERATION_QUEUE_POINTER;

Fig.3C.

5/28

System mail_system

2(5)

NEWTYPE CAUSE

literals T_overload, T_unknown;
FNDNEWTYPE CAUSE:

NEWTYPE OPERATION_STRUCT

struct owner pid; mbox_id_MBOX_AE

mbox_id MBOX_ADDRESS; class SERVICE_CLASS; info charstring:

info charstring; ENDEWTYPE OPERATION_STRUCT;

NEWTYPE OPERATION_QUEUE

array(OPERATION_QUEUE_POINTER,OPERATION_STRUCT) adding

operators

/*return true if there are no more operations */ is_last : OPERATION_QUEUE-> boolean;

/* add an operation to the queue - return true if queue is full */

add_op: OPERATION_QUEUE, OPERATION_STRUCT->boolean;

/* delete the current operation from the queue

- return true if queue is empty */

delete_op: OPERATION_QUEUE ->boolean;

/* get the first operation structure in the list */
get_first_op : OPERATION_QUEUE -> OPERATION_STRUCT;

/* get the next operation structure in the list */ get_next_op : OPERATION_QUEUE -> OPERATION_STRUCT;

ENDNEWTYPE OPERATION_QUEUE;

Fig.3d.

6/28

3(5)System mail_system NEWTYPE MBOX STRUCT struct class SERVICE CLASS mbox_id MBOX_ADDRESS; process_id pid; opener_id pid; opener_set_class SERVICE_CLASS; next_in_list MBOX_POINTER; queue boolean: op_queue OPERATION_QUEUE; ENDNEWTYPE MBOX_STRUCT; NEWTYPE MBOX_LIST arrav(MBOX ADDRESS, MBOX STRUCT) adding operators /* return true if there are no more mailboxes */ is last: MBOX LIST-> boolean; /* add an open mailbox structure to the list - return true if list is full */ add mbox: MBOX LIST, MBOX STRUCT-> boolean: /* update an open mailbox struct to the list - return true if fist is full */ update_mbox : MBOX_LIST , MBOX_STRUCT -> boolean; /* delete an open mailbox structure from the list */ delete_mbox : MBOX_LIST, MBOX_STRUCT -> boolean; /* get the first open mailbox structure in the list */ get_first_mbox : MBOX_LIST -> MBOX_STRUCT; /* get the next open mailbox structure in the list */ get_next_mbox : MBOX_LIST -> MBOX_STRUCT; /* get a specific open mailbox structure from the list */ get mbox : MBOX LIST, MBOX ADDRESS -> MBOX STRUCT; ENDNEWTYPE MBOX LIST: NEWTYPE RATE_STRUCT struct min_rate integer; max_rate integer; ENDNEWTYPE RATE_STRUCT; NEWTYPE RATE_ARRAY array(SERVICE_CLASS,RATE_STRUCT) ENDNEWTYPE RATE_ARRAY;

Fig.3e.

7/28

System mail_system

4(5)

SIGNAL /*---- SIGNALS for routes 1 -----*/
user_mailbox_open(MBOX_ADDRESS),
user_mailbox_close(MBOX_ADDRESS),
user_mailbox_close(MBOX_ADDRESS),
user_mailbox_closed(MBOX_ADDRESS),
user_mailbox_request(MBOX_ADDRESS),
user_mailbox_request(MBOX_ADDRESS, charstring),
user_mailbox_notification(MBOX_ADDRESS, CAUSE),
mail_application_overload_detected,
mail_application_overload_ceased;

SIGNAL. /"---- SIGNALS for route 2 ----*/
UM_open(pid,MBOX_ADDRESS),
UM_opened(MBOX_ADDRESS),
UM_opened(MBOX_ADDRESS),
UM_open_denied(MBOX_ADDRESS,CAUSE),
UM_request(OPERATION_STRUCT),
UM_notification(OPERATION_STRUCT),
Impose_UM_load_control(pid,SERVICE_CLASS),
queue_UM_requests(MBOX_ADDRESS);

SIGNAL /*---- SIGNALS for route 3 -----*/
queue_notifications,
resume_notifications,
stop_mailbox,
request(OPERATION_STRUCT),
notification(OPERATION_STRUCT);

SIGNAL /*---- SIGNALS for route 4 ----*/
transaction_rate(integer),
set_UM_class_bar(SERVICE_CLASS);

SIGNAL /*---- SIGNALS for route 5 -----*/
UM_service_class_query(MBOX_ADDRESS),
UM_service_class_result(MBOX_ADDRESS,SERVICE_CLASS);

SIGNAL /*---- SIGNALS internal to User_Mailbox -----*/
event(OPERATION_STRUCT);

SIGNALLIST Slist_1_out = user_mailbox_opened, user_mailbox_open_denied, user_mailbox_closed, user_mailbox_notification;

SIGNALLIST Slist_1_in = user_mailbox_open, user_mailbox_close, user_mailbox_request, mail_application_overload_detected, mail_application_overload_ceased;

SIGNALLIST Slist_2_out = UM_opened, UM_open_denied, UM_closed, UM_notification, queue_UM_requests, resume UM requests;

SIGNALLIST Slist_2_in = UM_open, UM_close, UM_request, impose_UM_load_control;

SIGNALLIST Slist_3_out = notification;

SIGNALLIST Slist_3_in = queue_notifications, resume_notifications, request, stop_mailbox;

SIGNALLIST Slist_4_out = set_UM_class_bar;

SIGNALLIST Slist_4_in = transaction_rate;

SIGNALLIST Slist_5_out = UM_service_class_query;

SIGNALLIST Slist_5_in = UM service class_result;





Fig.3g.

9/28











Fig.3i.



^{12/28} Fig.3j.




Fig.3k.







Fig.3l.



^{15/28} Fig.3m.








Fig.30.

Fig.3p.




Fig.3q.




Fig.3r.






Fig.3s.







Fig.3t.



BI (B) B) B)






Fig.3v.



25/28

Fig.3w.








Fig.3y.





Nixon & Vanderhye P.C. (10/99) (Domestic Non-Assigned/Foreign)

(Atty Dkt. No.

17 NOVEMBER 1999

οn

RULE 63 (37 C.F.R. 1.63) DECLARATION AND POWER OF ATTORNEY FOR PATENT APPLICATION IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if plural names as are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

[SSGXING PLATFORM]

as U.S. Application Serial No. GB99703831

the specification of which (check applicable box(s)):

was filed as PCT International application No.

is attached hereto

was filed on

X

and (if applicable to U.S. or PCT applicable	oplication) was amended on	
amendment referred to above. I as with 37 C.F.R. 1.56. I hereby clain listed below and have also identified	and understand the contents of the above identified specification, including the cl cknowledge the duty to disclose information which is material to the patentability on foreign priority benefits under 35 U.S.C. 119/365 of any foreign application(s) for sld below any foreign application for patent or inventor's certificate having a filing di fiority is claimed, before the filing date of this application:	f this application in accordance patent or inventor's certificate ate before that of the application on
Application Number 98309679.3	Country EP	Day/Month/Year Filed 25 NOVEMBER 1008
- 1/2	5 U.S.C. §119(e) of any United States provisional application(s) listed below. Date/Month/Year Filed	
the subject matter of each of the c	S.U.S.C. 120/365 of all prior United States and PCT international applications listed latims of this application is not disclosed in such prior applications in the manner p ty to disclose material information as defined in 37 C.F.R. 1.56 which occurred bet 2T international filing date of this application:	rovided by the first paragraph of 35
Prior U.S./PCT Application(s):	Day (Manth Wass Filed	Status: patented pending, abandoned
Application Serial No. PCT/GB99/03831	Day/Month/Year Filed	pending, abandones
PC1/GB99/03831	17 NOVEMBER 1999	
imprisonment, or both, under Sec- application or any patent issued the 8th Floor_Arlington_VA 22201-4 attomeys thereof (of the same ad- in the Patent and Trademark Offic Vanderhye_27026-3ames T. Hos- Bryan H. Davidson_30225-4 Stanle Bryan H. Davidson_30225-4 Stanle Robert A. Molan_26934-6 B. J. Sa Michelle N. Lester, 32311_Frank	terments were made with the knowledge that willful false statements and the like st tion 1001 of Title 18 of the United States Code and that such willful false statementen. And on behalf of the comer(s) hereof, I hereby appoint NIXON & VANDE 1700 of the comment	ts may jeopardize the validity of the sHYE P.C., I 100 North Glebe Rd., et directed), and the following licitation and to transact all business Larry S. Nixon, 25540, Robert A. 32458. Michael J. Keenan, 32466. H. Albard J. Keenan, 32466. H. Albard J. Keenan, 32466. H. Albard J. Keenan, 32469. H. Neison, 30481. John R. 32489. Man M. Kagen, 36178. delete any attorney rison, assignee, attorney, firm, or see: 22 Let December 1945.
Inventor:	MELVYN C BALE	BRITISH (citizenship)
Residence: (city) Post Office Address: (Zip Code)	1PSWICH CAX (state/country) GREA 23 DIGBY ROAD, 1PSWICH, SIIFPOLK 1P4 3NB	AT BRITAIN
Inventor's Signature: Inventor	GORDON HENDERSON	22 December 1999 BRITISH
,	KESGRAVE (first) (last) GRE	EAT BRITAIN (citizenship)
Residence: (city) Post Office Address:	51 THE LLOYDS, KESGRAVE, SUFFOLK	
(Zip Code)	IP5 2WH	
FOR ADDITIONAL INVENTORS	s, check box ☐ and attach sheet with same information and signature and c	late for each.